

DECLARATION OF PERFORMANCE
No. UPM11-4

1. Unique identification code of the product-type:
Machine strength graded structural timber which full fills the product standard EN 14081-1:2005+A1:2011
2. Identification of the construction product
UPM Strong, strength graded structural timber
3. Intended use of the construction product
Intended to be used for load bearing purposes in construction works.
4. Manufacturer's name and contact details:
UPM-Kymmene Oyj, Seikku Sawmill
28100 Pori, Finland
Tel. +358 204 14 153
www.upmtimber.com
6. System of assessment and verification of constancy of performance of the construction product:
System AVCP 2+
7. Certification

Notified factory production control certification body Inspecta Oy (No. 0416) performed:

- The initial inspection of the manufacturing plant and of factory production control;
- The continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control: No. 0416-CPR-4779.

9. Declared performance


Characteristic	Performance declaration	Harmonized technical standard
Species	Spruce (Picea abies), Pine (Pinus sylvestris)	EN 14081-1:2005+A1:2011
Growth area	Northern and North Eastern Europe	
Range of thickness	31 - 110 mm	
Range of width	60 – 300 mm	
Range of length	2,4 - 6,0 m	
Strength, stiffness and density	C18,C24,C30,C35, TR26,T15,T22	
Surface finish	Sawn and planed	
Dry or wet graded	Dry graded	
Reaction to fire	D-s2,d0	
Release of dangerous substances	NPD	
Durability as classification to: - wood destroying fungi - insects, termites - marine borers	Class 4 NPD NPD	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Matti Nordberg, Mill Director, Seikku Sawmill

29.10.2015

date and place


signature

